



## **Anti-Ambient Light**

Bright light sources, such as a window with exposure to direct sunlight, won't reduce the contrast of the projected image



## **High Accuracy Touch**

Infrared technology precise position

FX-82



### 10 Point Multi-Touch

Support for Ten simultaneous touches enables up to Tenusers to interact with the interactive whiteboard by using the pens or other objects, or by using their fingers to write and to perform gestures.



## **USB Power Supply**

Without external power supply, driven by USB 2.0 cable provides both a digital signal and power from your computer to your interactive whiteboard, you don't require an additional power supply.

#### **Touch and Gestures**

All board operations can be performed with finger touch or movement on the board surface. You can use the pen for writing and drawing. Both options offer smooth comfortable handwriting.

### **Quick Start Hot Keys**

## 18 Shortcut Keys on both side FX-82

You can easily select a tool from these shortcut keys to click, write, erase and so on.



# **INTERACTIVE SMART BOARD SOLUTION**

### **SPECIFICATIONS**

Model Number	SMART BOARD FX-82			
Outline Size	1722×1241×38 mm			
Inside Size	1606.5×1126.5 mm			
Display Ratio	4:3			
Toolbar	Two Sides ,18 Buttons Each Side			
Touch Technology	Infrared			
Response Object	Finger, Pen, any other Opaque Object			
Points Input	10			
Resolution	32768 * 32768			
Coordinate Accuracy	1.5mm			
Response Size	Ø 5 mm			
Cursor Speed	180 d/s			
Respond Speed	< 20 ms			
Board Material	Plastic Frame with Steel Surface, High Density with Polyfoam Core and Steel Back			
Projection Effect	Excellent with Low Glare			
System Support	Windows 7/8/10, Linux Ubuntu 14.04/15.04, Android 4.0 and up, Mac 10.5 and up Version			
Interface	USB 2.0/3.0			

		ACCESSO	ORIES LIST (S	TANDARD)		
USB Cable 5M, A-A	Pens	Extend Pen	Eraser	Application CD	Wall Mount Bracket & Screws	Quick Installation Pointor Guide
O	111				1111 9994	

	PACKAGE INFORMATION	
Model number	FX-82	
Packing Type	Cartons Box	
Package Size	T.B.D	
Net Weight	15±2KG	
Gross Weight	22±2KG	

POWER SUPPLY			
Power Supply	USB Power Supply		
Voltage	DC 5V, +4.75V to +5.25V		
Power Consumption	<2W (200mA)		

ENVIRONMENT DA	ATA		
Temperature	Working Temperature:	-20°C ~ 70°C	
	Storage Temperature:	-40°C ~ 85°C	
Humidity	Working Humidity:	90%	
	Storage Humidity:	90%	

<sup>\*</sup>Specification are subject to changed without any notice



